STAT	SUBJ: Contract
•	Gentlemen:
STAT	This proposed program outlines the necessary redesign, fabrication, assembly and testing to provide a Processor acceptable to the sponsor. These modifications will enable us to adequately process film aerographic duplicating film and film fine grain aerial duplicating film.
	I. Replenishing System

The replenishing system will consist of 4 flow meters sufficient in size to process the above mentioned film types. Each processing module will be modified by the addition of overflow stand pipes.

II. Temperature Control and Indicating System

The temperature indicating system will be tested for accuracy and reliability. If the present system proves unusable, it will be replaced with a thermister-operated system.

Our intention will be to elevate the processing temperature well above ambient, creating enough temperature difference as to eliminate the need for a refrigeration system in the processor.

III. Positive Pressure

August 27, 1968

The bubbling problem causing the processing solutions to overflow onto the pumps may be eliminated by increasing the amount of anti-foam agent used in these solutions. If this simple test proves negative, it will become necessary to increase the exhaust duct size, to reduce the positive pressure build-up under each module cover.

Declass Review by NIMA/DOD

STAT

STAT

IV. Film Transport Indicating System

The film transport indicating system will consist of an independent tachometer and an FPM indicating meter mounted adjacent to the speed control knob on the front panel.

V. <u>Drain Problem</u>

The drain outlet size will be increased to accommodate draining all modules at one time.

VI. Dryer

There are two possible design approaches to the drying problem which shall be shall be studied.

- A The simplest modification appears to be the addition of a second infra red source which will be installed so that the radiation is applied to the emulsion as well as the base side of the film.
- B In the event the infra dryer proves unsatisfactory a conventional type dryer will be used.

VII. Acceptance Test Criteria

A - Reference Film Samples

Film samples will be sensitometrically exposed and processed under controlled conditions in accordance with the film manufacturer's recommendations. The resultant D log E curves for each film type will be used as a basis to evaluate the performance of the processor.

B - Processing Parameters

Sufficient film will be exposed under the same conditions as the reference film samples and processed to the proper Time – Temperature and Type of chemistry to produce D log E curves that approach those obtained with the reference film samples. The gamma will be equivalent to the reference. Photographic speed will be within 1 stop. Uniformity of development will show a density variation of no more than ± 0.05 density units at an average density of 1.00 on a 9 1/2" X 9 1/2" film sample.

-3-

August 27, 1968

The parties recognize that the performance requirements in this redesign plan are within the original scope of the contract. The successful demonstration of film processing capability shall constitute acceptance of the Sepratron Processor. This program may be completed within six months from your acceptance of this proposal.

	Sincerely yours,									
STAT										
·•										

	14	Арр	LO Men	AF GF	RRefe	ASE 126	U27 0	964 <i>ST</i>	, CY	₽₽D	P78E	3647	I7A00240	0060
				RC R3	R4	R5	Ró	R7	7R8	R9	RI	0		
то	CO	R1 AE AND/O	R2 R SYMBO					BUILDING	, ROOM	, ETC.				
1.	NA.	AL A110/ 5												
_ [<u>N f I</u>	<u>C</u>												
2.													1	
					⊢†									
3.														
4.						14								
						 								
5.													ļ	
	LLOTMENT	SYMBOL		Пн	ANDLE DI	RECT				-	AND DE			
	APPROVAL			□ IA	MEDIATE	ACTION			L] RECO	MMENDA	ATION		
	S REQUEST	ED			IITIALS				Ľ	_	ATURE			
	CONCURREN			-	IECESSARY IOTE AND					YOUR	COMM	ENT	1	
	CORRECTION	1			ER OUR C		TION			YOUR	INFOR	NOITAM		
,	FILING FULL REPORT	ī			ER TELEPH			MOIT	L	لـ				
	ANSWER OF		/L-											
- 1														
DEM	THE SIGNAT	TURE OF	- T -											
	Cont	rac	r					,	<i>[</i>]	\rfloor				
	PREPARE RETHE SIGNAL ARKS CONT ARKS ARKS	Cea	iel	fl	ind	all	ac	hed	y c	of	8			
ر ا	<i>p</i>		$\neg R$	ed	esi	gn	Pr	spo	2al					
1%	<u> </u>				0	1.	-	,	0-	To b	7 8-5-	m	1	
C	omm	um	nca	M	L -	70 X	Jo.		8					
	1/3/6	8												
	11.210	0												
1													1	
-	,		÷											
			1 R	2 0	3 R	4 R5	5	Ró I	R7	R8	R9	R10		
	OM NO							ROOM, E	TC.					
	I	1		. –	_ ^/	2 -	PALENT			DATE	Z	<u> </u>		
	110	\nearrow App	royec	ı For	Refe	rse ZC	かりん	16/17	: CIA	\-K £ X	<i>y (</i> 86	su4/74	ŀ7 / I00240	IUU6(